


U.2 male to M.2 M-Key U.2 female Adapter with 3.5" Housing



Notice: Both M.2 SSD or U.2 SSD insert into PU412G, only one can work, U.2 SSD would be priority.

Features

- ※ M.2 NVMe to U.2(SFF-8639) convert
- ※ U.2(SFF-8639) convert
- ※ Build in M.2 M-key Female connector
- ※ Build in SFF-8639 plug & receptacle connector, pin-out defined by PCIe
- ※ PWM synchronous buck converter Power IC for M.2 NVMe SSD
- ※ 4A maximum output current
- ※ Short circuit protection
- ※ In-rush current suppression
- ※ Thermal shutdown protection
- ※ ESD HBM (Human Body Mode)/2KV
- ※ LED1 Green LED on indicates U.2 SSD power ready
- ※ LED2 RED LED Blinking indicates U.2 SSD active status
- ※ LED3 Green LED on indicates M.2 NVMe SSD power ready
- ※ LED4 RED LED Blinking indicates M.2 SSD active status

Specifications

- ※ Compliant with NVM Express 1.2a
- ※ Support PCI Express Base Specification Rev 3.0
- ※ Support SSD_Form_Factor_Version1_a
- ※ Compliant with PCI Express M.2 Specification Version 1.0
- ※ Compliant with SFF-8639 Specification Rev 2.0
- ※ Compliant with SFF-83 Specification for 3.5" Form Factor Drive Dimensions
- ※ Compliant with SFF-8323 Specification Rev 1.6 for 3.5" Form Factor Drive with Serial Attached Connector

Specifications

- ※ Type 2242-D2-B-M: 42mm(L) x 22mm(W)
- ※ Type 2260-D2-B-M: 60mm(L) x 22mm(W)
- ※ Type 2280-D2-B-M: 80mm(L) x 22mm(W)
- ※ Type 22110-D2-B-M: 110mm(L) x 22mm(W)