



PU418G Converter Card

Performance & Burn In Test Rev. 1.0

Table of Contents

- 1. Overview**
- 2. Performance Measurement Tools and Results**
 - 2.1 Test Platform
 - 2.2 Test target and M.2 NVMe SSD
 - 2.3 Install Hardware
 - 2.4 BIOS & Windows 10 OS environment setup
 - 2.5 CrystalDiskMark 6.0.0 x64 performance test
 - 2.6 AS SSD Benchmark 1.9 performance test
 - 2.7 ATTO Disk Benchamrk 3.0.5 performance test
 - 2.8 AnvilBenchmark_V110_B337 Benchmark performance test
- 3. Burn In Tests and Results**
 - 3.1 BurnInTest v8.1 Pro burn in test
- 4. Summary**

PU418G Converter Card

1. Overview


PU418G adapter, providing M.2 M-key connector can be M.2 (PCI-e I/F NVMe) SSD converted into U.2(SFF-8639), PCI-e Gen 3 / 4 Lanes interface.

2. Tools and Results of Performance Measurement

2.1 Test Platform

M/B : GIGABYTE **Z170X UD5 TH**
CPU : Intel **i5-6500**, 3.2GHz/ 6M Cache/ LGA1150
Memory : Kingston **KVR21N15D8/8, DDR4-2133MHz, 16G**(8GB DIMM*2)
ATX Power : COOLER MASTER G750M, **750W ATX**, 12V V2.2 Power Supply
Graphic : Z170 Chipsets built-in **HD Graphics 530**
Adapter: PE0404 PCIe to SFF-8643 Mini SAS HD Cable
Cable: Amphenol SFF-8643 to U.2(SFF-8639) Cable
OS : Microsoft **Windows 10 64bit OS**

2.2 Test target: PU418G adapter & Samsung SM961 **512GB NVMe SSD**



2.3 Install Hardware

Insert M.2 SSD into PU418G converter's M.2 M-key connector, and then connect PU418G converter to PE0404 adapter(PCI-e 4-lane to SFF-8643 Mini SAS HD), using SFF-8643 to U.2(SFF-8639) cable. PE0404 adapter plugs into **PCI-e slot of Z170X UD5 TH**.

2.4 BIOS & Windows 10 OS environment setup


2.4.1 Install Windows 10 64bit OS into PU418G

PU418G Converter Card

2.5 CrystalDiskMark 6.0.0 x64 performance test

※Benchmark (Sequential Read & Write / default = 1MB)


2.5.1 Show Samsung SM961 M.2(NVMe)/512GB performance as below:



2.6 AS SSD Benchmark 1.9 performance test

※Benchmark (Read & Write by MB/s, default block size = 16MB)


2.6.1 Show Samsung SM961 M.2(NVMe)/512GB performance as below:



PU418G Converter Card


2.7 ATTO Disk Benchamrk 3.0.5 performance test

2.7.1 Show Samsung SM961 M.2(NVMe)/512GB performance as below:



2.8 AnvilBenchmark_V110_B337

2.8.1 Show Samsung SM961 M.2(NVMe)/512GB performance as below:





PU418G Converter Card

3. Burn In Tests and Results


3.1 BurnInTest v8.1 Pro for Samsung SM961 M.2(NVMe)/512GB SSD

3.1.1 system information as below:




PU418G Converter Card

3.1.2 show Disk test mode(10 ways cycle test)



3.1.3 show 24-hour Burn-in test PASSED



PU418G Converter Card

4. Summary

- 4.1 M.2 NVMe SSD is PCI-e Gen 3 / 4 Lanes Interface, I/O speed, max. to 4GB.
- 4.2 PU418G adapter I/O performance is based on M.2 NVMe SSD.